

## CLAIMS

What is claimed is:

Sub 1. A quick release system for mounting a backrest on a motorcycle, the system comprising:

5 a side bracket plate having a first notch extending inwardly generally horizontally from an end of the side bracket plate, and a second notch extending generally upwardly into the side bracket plate from a bottom thereof, the first and second notches being configured to receive a bolt head;

10 a slidable retaining means mounted to the side bracket plate for selectively allowing movement of a bolt head into the second notch.

15 2. The quick release system according to claim 1, further comprising at least one semi-circular grommet disposed along one of the notches.

20 3. The quick release system according to claim 1, wherein the slidable retaining means comprises a retaining pin slidable between a first position, wherein the pin prevents movement of a bolt head out of the second notch, and a second position, wherein the retaining pin does not prevent movement of a bolt head and out of the second notch.

4. The quick release system according to claim 3, wherein the retaining pin is biased into the first position.

5. The quick release system according to claim 3, further comprising a handle attached to the retaining pin such that movement of the handle away from the second notch moves the retaining pin from the first position to the second position.

Sub A1> 6. The quick release system according to claim 4, further comprising a locking means disposed in the handle.

Sub C1> 7. The quick release system according to claim 6, wherein the locking means comprises a locking pin.

8. The quick release system according to claim 6, wherein the side bracket plate has a locking hole and wherein the locking pin extends into the locking hole to prevent movement of the handle.

9. The quick release system according to claim 6, wherein the side bracket plate has a locking notch and wherein the locking pin extends into the locking notch to prevent

movement of the handle away from the second notch.

5      ~~Sub A~~ 10.    The quick release system according to claim 6,  
wherein the locking pin is spring loaded to bias the locking  
pin into a locking position.

10      ~~Sub C~~ 11.    The quick release system according to claim 6,  
wherein the side bracket plate further comprises a guide  
channel formed therein, and wherein the handle slides along  
the guide channel.

15      12.    The quick release system according to claim 1,  
further comprising locking means for selectively preventing  
movement of the slidable retaining means.

13.    The quick release system according to claim 12,  
wherein the locking means comprises a locking pin.

20      14.    The quick release system according to claim 13,  
wherein the side bracket plate has a locking hole and wherein  
the locking pin extends into the locking hole to prevent  
movement of the retaining means.

Sub A3> 15. The quick release system according to claim 13, wherein the side bracket plate has a locking notch and wherein the locking pin extends into the locking notch to prevent movement of the handle away from the second notch.

5

Sub C1> 16. The quick release system according to claim 13, wherein the locking pin is spring loaded to bias the locking pin into a locking position.

10

17. The quick release system according to claim 1, wherein the system further comprises at least one bolt, the bolt having a bolt head with a generally annular channel formed therein, the bolt head being configured for nesting in the second notch.

15

18. The quick release system according to claim 17, wherein the system comprises two bolts each having a generally annular channel formed therein and each being configured for nesting in one of the first and second notches.

20

Sub A4> 19. The quick release system according to claim 17, wherein the head bolt further comprises a second annular channel.

sub c1> 20. The quick release system according to claim 17,  
wherein the bolt head further comprises female threaded  
portion.

5 21. A side bracket plate for use in a backrest quick  
release system, the side bracket plate comprising:

a first notch configured for receiving a bolt head;

a second notch having an opening and being configured for  
receiving a bolt head;

10 a retaining pin positioned adjacent to the second notch,  
the retaining pin being movable between a first position  
wherein the retaining pin prevents a bolt head disposed in the  
second notch from being removed from the second notch, and a  
second position wherein the retaining pin does not prevent  
15 removal of the bolt head.

22. The side bracket plate according to claim 21,  
wherein the retaining pin is spring loaded.

20 23. The side bracket plate according to claim 21,  
further comprising a handle attached to the retaining pin for  
selectively moving the retaining pin between the first and  
second positions.

09749-01260  
FO9270" 6TF460

24. The side bracket plate according to claim 21, further comprising a locking means for selectively preventing movement of the retaining pin from the first position to the second position.

25. The side bracket plate according to claim 24, wherein the locking means comprises a locking pin configured to engage the side bracket plate.

26. The side bracket plate according to claim 25, wherein the side bracket plate has a locking hole and the locking pin is configured for placement into the locking hole to prevent movement of the retaining pin.

27. The side bracket plate according to claim 25, wherein the side bracket plate has a locking notch formed therein and wherein the locking pin is configured for advancement into the locking notch.

add A6 >